

# Switch Engine™ v33.1.1 Licensing Guide

Comprehensive Licensing Features and Installation

9039056-00 Rev AA August 2024



Copyright © 2024 Extreme Networks, Inc. All rights reserved.

#### **Legal Notice**

Extreme Networks, Inc. reserves the right to make changes in specifications and other information contained in this document and its website without prior notice. The reader should in all cases consult representatives of Extreme Networks to determine whether any such changes have been made.

The hardware, firmware, software or any specifications described or referred to in this document are subject to change without notice.

#### **Trademarks**

Extreme Networks and the Extreme Networks logo are trademarks or registered trademarks of Extreme Networks, Inc. in the United States and/or other countries.

All other names (including any product names) mentioned in this document are the property of their respective owners and may be trademarks or registered trademarks of their respective companies/owners.

For additional information on Extreme Networks trademarks, see: https://www.extremenetworks.com/about-extreme-networks/company/legal/trademarks

#### **Open Source Declarations**

Some software files have been licensed under certain open source or third-party licenses. End-user license agreements and open source declarations can be found at: https://www.extremenetworks.com/support/policies/open-source-declaration/



# **Table of Contents**

Preface	4
Text Conventions	∠
Related Publications	6
Switch Engine Publications	E
Open Source Declarations	6
Send Feedback	6
Help and Support	6
Subscribe to Product Announcements	7
License Overview	8
Overview for Universal Hardware Switches	9
Feature Licenses	
Additional General License Information	
Installing and Uninstalling Licenses on Universal Switches	
Obtaining and Installing Licenses	
Uninstalling Licenses Temporarily	
Transferring Licenses	
Displaying the Installed License Levels and Feature Licenses	
Factory Default (Evaluation) License for Universal Hardware Switches	12
Switch License Features	
Base License Features	
Premier License Features	16
Feature Licenses	18
MACsec Platform Support	
ExtremeCloud IQ Platform Support	
Network Timing Feature License	
MAC Security Feature License	23



## **Preface**

Switch Engine v33.1.1 Feature License Requirements by Extreme Networks, Inc., released in August 2024, explains the license levels and feature licenses available for universal hardware switches, and lists the features that they support.

Read the following topics to learn about:

- The meanings of text formats used in this document.
- · Where you can find additional information and help.
- · How to reach us with questions and comments.

## **Text Conventions**

Unless otherwise noted, information in this document applies to all supported environments for the products in question. Exceptions, like command keywords associated with a specific software version, are identified in the text.

When a feature, function, or operation pertains to a specific hardware product, the product name is used. When features, functions, and operations are the same across an entire product family, such as Extreme Networks switches or SLX routers, the product is referred to as *the switch* or *the router*.

Table 1: Notes and warnings

Icon	Notice type	Alerts you to
-	Tip	Helpful tips and notices for using the product
<b>600</b>	Note	Useful information or instructions
-	Important	Important features or instructions
1	Caution	Risk of personal injury, system damage, or loss of data
<b>A</b>	Warning	Risk of severe personal injury

Preface Text Conventions

#### **Table 2: Text**

Convention	Description
screen displays	This typeface indicates command syntax, or represents information as it is displayed on the screen.
The words <i>enter</i> and <i>type</i>	When you see the word <i>enter</i> in this guide, you must type something, and then press the Return or Enter key. Do not press the Return or Enter key when an instruction simply says <i>type</i> .
<b>Key</b> names	Key names are written in boldface, for example <b>Ctrl</b> or <b>Esc</b> . If you must press two or more keys simultaneously, the key names are linked with a plus sign (+). Example: Press <b>Ctrl+Alt+Del</b>
Words in italicized type	Italics emphasize a point or denote new terms at the place where they are defined in the text. Italics are also used when referring to publication titles.
NEW!	New information. In a PDF, this is searchable text.

## **Table 3: Command syntax**

Convention	Description
bold text	Bold text indicates command names, keywords, and command options.
<i>italic</i> text	Italic text indicates variable content.
[ ]	Syntax components displayed within square brackets are optional.
	Default responses to system prompts are enclosed in square brackets.
{ x   y   z }	A choice of required parameters is enclosed in curly brackets separated by vertical bars. You must select one of the options.
ж   у	A vertical bar separates mutually exclusive elements.
< >	Nonprinting characters, such as passwords, are enclosed in angle brackets.
	Repeat the previous element, for example, member [member].
\	In command examples, the backslash indicates a "soft" line break. When a backslash separates two lines of a command input, enter the entire command at the prompt without the backslash.

Related Publications Preface

## **Related Publications**

### Switch Engine Publications

- Switch Engine v33.1.1 Command Reference Guide
- Switch Engine v33.1.1 Feature License Requirements
- Switch Engine and ExtremeXOS v33.1.1 EMS Messages Catalog
- Switch Engine v33.1.1 User Guide
- Switch Engine v33.1.1 Release Notes
- ExtremeXOS Quick Guide
- Extreme Hardware/Software Compatibility and Recommendation Matrices
- Extreme Optics Compatibility
- Switch Configuration with Chalet for ExtremeXOS 21.x and Later
- ACL Solutions Guide
- ExtremeXOS and Switch Engine SNMP Traps Reference

### Open Source Declarations

Some software files have been licensed under certain open source licenses. More information is available at: www.extremenetworks.com/support/policies/open-source-declaration/.

### Send Feedback

The User Enablement team at Extreme Networks has made every effort to ensure that this document is accurate, complete, and easy to use. We strive to improve our documentation to help you in your work, so we want to hear from you. We welcome all feedback, but we especially want to know about:

- Content errors, or confusing or conflicting information.
- Improvements that would help you find relevant information.
- · Broken links or usability issues.

To send feedback, email us at documentation@extremenetworks.com.

Provide as much detail as possible including the publication title, topic heading, and page number (if applicable), along with your comments and suggestions for improvement.

## Help and Support

If you require assistance, contact Extreme Networks using one of the following methods:

Extreme Portal

Search the GTAC (Global Technical Assistance Center) knowledge base; manage support cases and service contracts; download software; and obtain product licensing, training, and certifications.

#### The Hub

A forum for Extreme Networks customers to connect with one another, answer questions, and share ideas and feedback. This community is monitored by Extreme Networks employees, but is not intended to replace specific guidance from GTAC.

#### Call GTAC

For immediate support: (800) 998 2408 (toll-free in U.S. and Canada) or 1 (408) 579 2800. For the support phone number in your country, visit www.extremenetworks.com/support/contact.

Before contacting Extreme Networks for technical support, have the following information ready:

- Your Extreme Networks service contract number, or serial numbers for all involved Extreme Networks products
- · A description of the failure
- · A description of any actions already taken to resolve the problem
- A description of your network environment (such as layout, cable type, other relevant environmental information)
- Network load at the time of trouble (if known)
- The device history (for example, if you have returned the device before, or if this is a recurring problem)
- Any related RMA (Return Material Authorization) numbers

#### Subscribe to Product Announcements

You can subscribe to email notifications for product and software release announcements, Field Notices, and Vulnerability Notices.

- 1. Go to The Hub.
- 2. In the list of categories, expand the **Product Announcements** list.
- 3. Select a product for which you would like to receive notifications.
- 4. Select Subscribe.
- 5. To select additional products, return to the **Product Announcements** list and repeat steps 3 and 4.

You can modify your product selections or unsubscribe at any time.



# **License Overview**

The switches supported on Switch Engine 32.7 include two different license levels: Base and Premier.

The following figure illustrates that the Premier license level builds on the features of the Base license, or the Base license is the only license level available.




Figure 1: License Levels for Switches Supported on Switch Engine 32.7

In previous releases, non-Universal Hardware and Universal switch license levels correlated in the following way:

Premier = Core

Base = Advanced Edge + AVB



# Overview for Universal Hardware Switches

Installing and Uninstalling Licenses on Universal Switches on page 10 Displaying the Installed License Levels and Feature Licenses on page 12 Factory Default (Evaluation) License for Universal Hardware Switches on page 12

This document explains the license levels and feature licenses available for universal hardware switches, and lists the features that they support.

Switch Engine software supports the following license levels for the universal hardware switches:

- Base—included as standard (see Base License Features on page 13)
- Premier (see Premier License Features on page 16)

The Base license provides a basic feature set and the Premier license adds additional functionality.

Table 4: Standard and Upgrade Licenses for Universal Hardware Switches

Switch platform	Base	Premier
ExtremeSwitching 5320	Standard	Upgrade
ExtremeSwitching 5420	Standard	Upgrade
ExtremeSwitching 5520	Standard	Upgrade
ExtremeSwitching 5720	Standard	Upgrade
Extreme Networks 7520	Standard	Upgrade
Extreme Networks 7720	Standard	Upgrade

#### Feature Licenses

To supplement the license levels, additional capabilities can be added by purchasing feature licenses (see Feature Licenses on page 18).

## Additional General License Information

Software licenses are stored in the EEPROM and, after enabled, persist through reboots, software upgrades, power outages, and reconfigurations. The keys are unique to the switch, but can be transferred (see <u>Transferring Licenses</u> on page 11).

If you attempt to execute a command and you either do not have the required license or have reached the limits defined by the current license level, the system displays one of the following messages:

```
Error: This command cannot be executed at the current license level. Error: You have reached the maximum limit for this feature at this license level.
```

## Installing and Uninstalling Licenses on Universal Switches

This section explains how to obtain and install/uninstall licenses on universal hardware switches.

## Obtaining and Installing Licenses

For universal hardware switches, you can activate a license on the switch using either of the following methods:

- 1. Manual activation by obtaining the license activation file from Support Portal.
- 2. Automated activation using ExtremeCloud IQ. For information about using ExtremeCloud IQ for bulk automated license activation, go to https://www.extremenetworks.com/support/documentation/extremecloud-iq/.

For manual license generation and installation:

- Follow manual activation instructions for license generation available on the Extreme Portal: Products > Products Home > ExtremeSwitching > Universal > EXOS (for your switch) > Activation Instructions.
- 2. Load the license file onto the switch using either of the following commands:

```
download [url url {vr vrname} | image [active | inactive] [[hostname |
ipaddress] filename {{vr} vrname} {block_size block_size}] {partition}
{install {reboot}}
```

```
tftp get [ ip-address | host-name] { vr vr_name } { block-size
block_size } remote-file local-file} {force-overwrite}
```

To copy from a USB: cp old\_name new\_name specifying /usr/local/ext. For example: cp /usr/local/ext/old name /usr/local/cfg/new name.

You can place the license file anywhere within the user-visible file system (for example: /usr/local/\*).

3. To install the license, use the following command:

```
install license file filename {slot slot}
```

This command installs all of the license features contained in the selected license file to the specified slot (node).

#### Uninstalling Licenses Temporarily

You can temporarily uninstall a license from a switch. This enables you to retain the license entitlement on the switch, and thus, the original license can be used to reinstall the license. You can use this option to temporarily disable a license.

To uninstall a license temporarily from a universal hardware switch, use the following command:

```
uninstall license file filename [{revoke revocation_file} | withhold ] {slot slot} using the withhold option.
```

To temporarily uninstall a specific license feature, such as MAC Security (MACsec), from a universal hardware switch, use the following command:

```
uninstall license product product_name [revoke revocation_file | withhold] {slot slot} using the withhold option.
```

### **Transferring Licenses**

You can permanently remove a license, which enables you to transfer the license to another switch. This should only be done when preparing to return a defective switch for a replacement switch (RMA).

The uninstall license file *filename* command accepts *filename* as a .lic file that contains one or more licenses to be uninstalled. This is the license file that was used to install license.

The uninstall license product *product\_name* command accepts *product\_name* as the name of the license product to be uninstalled. This is the product name as it appears with the **show licenses** command.

• To uninstall a license permanently from a universal hardware switch, use the following command:

```
uninstall license product product_name [revoke revocation_file | withhold] {slot slot} using the revoke option.
```

• To permanently uninstall a specific license product, such as PRD-5000-MACSEC, from a universal hardware switch, use the following command:

```
uninstall license product product_name [revoke revocation_file | withhold] {slot slot} using the revoke option.
```

The **revoke** option invalidates the feature license and generates a revocation certificate, which is the first step to release the license entitlement back to the license entitlement manager (LEM). If the specified file name (for <code>revocation\_file</code>) does not have an <code>.rvk</code> extension, it is automatically appended.

To transfer a license from a defective unit to a working unit:

- 1. Go to the Extreme Portal.
- Select Asset > Licenses Home.
- 3. Select License Transfer.
- 4. Enter the serial numbers of the defective unit and the replacement unit, and the RMA/case number.

## Displaying the Installed License Levels and Feature Licenses

You can display the license level and feature licenses installed on your Extreme Networks switch by using the show licenses {[slot slot |all]} {detail} command.

## Factory Default (Evaluation) License for Universal Hardware Switches

New universal hardware switches include a Factory Default (Evaluation) License to use all features (excluding MACsec). This Evaluation license is equivalent to a Premier license. You can configure all features, except MACsec, without restrictions and save the configuration.

The evaluation period is 30 days. If after 30 days you have not obtained and installed a Premier license (see Obtaining and Installing Licenses on page 10) and you reboot the switch, the switch will effectively have only Base license (see Table 4 on page 9) capabilities.

To extend the evaluation period, you can use the following commands:


To enable a trial license, issue the command debug epm enable trial-license.

To clear a trial license, issue the command debug epm clear trial-license. A reboot is required before the clear license takes effect.



#### Note

Enabling a newly obtained license requires clearing the trial license, and then rebooting the switch.



# **Switch License Features**

Base License Features on page 13
Premier License Features on page 16

## Base License Features

The Base License includes the features in the following table:

### **Table 5: Switch Engine Base License Features**

Switch Engine Software Feature	Supported Platforms
<ul> <li>AVB</li> <li>Generalized Precision Time Protocol (GPTP)</li> <li>Multiple VLAN Registration Protocol (MVRP)</li> <li>Multiple Stream Registration Protocol (MSRP)</li> <li>Platform Support</li> </ul>	All platforms, except 4120, 4220, 5320-XT, 7520, and 7720. Universal platforms have the AVB Feature License included in the Advanced Edge or Base License. You do not need to separately purchase and install the AVB Feature License for these switches.
BGP Auto-peering	All platforms
BGP peers—Switches are allowed up to 2 manually configured BGP peers on the default VR with a base license.	All platforms
CLEARFlow	All platforms
Convergence End Point (CEP) detection	All platforms
DHCPv4:  DHCPv4 server  DHCv4 client  DHCPv4 relay  DHCPv4 smart relay	All platforms
DHCPv6: DHCPv6 relay DHCPv6 prefix delegation snooping DHCPv6 client DHCPv6 smart relay DHCPv6 remote ID	All platforms

Base License Features Switch License Features

**Table 5: Switch Engine Base License Features (continued)** 

Switch Engine Software Feature	Supported Platforms
Direct Attach—based on the IEEE version of VEPA, eliminates the virtual switch layer, simplifying the network and improving performance. Direct Attach enables data center simplification by reducing network tiers from four or five tiers to just two or three tiers, depending on the size of the data center.	All platforms
EAPS Advanced Edge—multiple physical rings, and "common links", also known as "shared port".	All platforms except 4120 and 4220
ERPS-more domains (allows 32 rings with matching ring ports) and multi-ring support	All platforms except 4120 and 4220
ESRP-Full	All platforms
ESRP-Virtual MAC	All platforms
Extended Edge Switching	5420, 5520, and 7520-48Y
Extreme Network Virtualization (XNV)	All platforms except 5320, 4120 and 4220
Fabric Attach—uses the IEEE802.1ab Link Layer Discovery Protocol (LLDP) extensions to automatically attach network devices to individual services in an IEEE 802.1aq Shortest Path Bridging (SPB) network:  • Fabric Attach Proxy  • Fabric Attach Client  • Fabric Attach Server  • Standalone Proxy	All platforms
<ul><li>IP address security:</li><li>DHCP snooping</li><li>Trusted DHCP server</li><li>Source IP lockdown</li><li>ARP validation</li></ul>	All platforms
IP Flow Information Export (IPFIX)	5420, 5520, 5720
IP NAT	7520, 7720
<ul> <li>IP security:</li> <li>DHCP Option 82—L3 mode</li> <li>DHCP Option 82—L3 mode VLAN ID</li> <li>Disable ARP learning</li> <li>Gratuitous ARP protection</li> <li>DHCP secured ARP / ARP validation</li> <li>Source IP lockdown</li> </ul>	All platforms
IPv4 unicast routing, including static routes	All platforms

Switch License Features

Base License Features

**Table 5: Switch Engine Base License Features (continued)** 

IPV4 multicast routing, including static routes  Note: This feature has limitations in the Edge and Advanced Edge licenses. See the Switch Engine v33.11 User Guide.  IPV4 Duplicate Address Detection (DAD)  IPV6 unicast routing, including static routes  IPV6 interworking—IPV6-to-IPV4 and IPV6-in-IPV4 configured tunnels  IPV6 DAD without CLI management  IPV6 DAD without CLI management  IPV6 DAD without CLI management  IPV6 DAD with CLI management  III platforms  III platforms  IPV6 DAD with CLI management  III platforms  III platforms except 4120 and 4220  III platforms  IIII platforms  IIII platforms  IIII platforms  III	Switch Engine Software Feature	Supported Platforms
Note: This feature has limitations in the Edge and Advanced Edge licenses. See the Switch Engine v33.11 User Guide.  IPv4 Duplicate Address Detection (DAD)  IPv6 unicast routing, including static routes  IPv6 interworking—IPv6-to-IPv4 and IPv6-in-IPv4 configured tunnels  IPv6 DAD without CLI management  IPv6 DAD without CLI management  IPv6 DAD with CLI management  All platforms  IPv6 DAD with CLI management  IPv6 DAD with CLI management  All platforms  IPv6 DAD with CLI management  IPv6 DAD with CLI management  All platforms  IPv6 DAD with CLI management  All platforms except 4i20 and 4220  All platforms  IPv6 DAD with CLI management  IPv6 DAD with CLI management  All platforms  IPv6 DAD with CLI management  All		
Edge and Advanced Edge licenses. See the Switch Engine v33.11 User Guide.  IPV4 Duplicate Address Detection (DAD)  IPV6 unicast routing, including static routes IPV6 interworking—IPV6-to-IPV4 and IPV6-in-IPV4 configured tunnels IPV6 DAD without CLI management IPV6 DAD without CLI management All platforms IPV6 DAD with CLI management All platforms IPV6 DAD with CLI management All platforms IPV6 DAD with CLI management All platforms  Keychain Manager All platforms Local-only, user-created virtual routers (VR) Multi-Switch Link Aggregation Group (MLAG) All platforms except 4120 and 4220 Multinetting for forwarding All platforms ONEPolicy All platforms ONEPv2-Edge (limited to max of 4 active interfaces) OSPFV2-Edge (limited to max of 4 active interfaces) All platforms except 4120 and 4220 INDEPV3-Edge (limited to max of 4 active interfaces) All platforms except 4120 and 4220 All platforms except 4120 and 4220 All platforms except 4120 and 4220 INDEPV3-Edge (limited to max of 4 active interfaces) All platforms except 4120 and 4220 All platforms Event 4120 and 4220 All plat		All platforms
IPv6 unicast routing, including static routes IPv6 interworking—IPv6-to-IPv4 and IPv6-in-IPv4 configured tunnels IPv6 DAD without CLI management IPv6 DAD with CLI management All platforms Keychain Manager Local-only, user-created virtual routers (VR) Multi-Switch Link Aggregation Group (MLAG) Multinetting for forwarding ONEPolicy OSPFv2-Edge (limited to max of 4 active interfaces) OSPFv2 Auto-peering OSPFv3-Edge (limited to max of 4 active interfaces) PIM—Universal switches are not subject to the maximum number of PIM IPv4 interfaces (4) that pertains to other switch models. PIM-SM-Edge PIM snooping Note: This feature has limitations in the Base license. See the Switch Engine v33.11 User Guide. Policy based routing (PBR) for IPv4 Policy based routing (PBR) for IPv6 Protocol-based VLANS PIPvg All platforms All platforms All platforms except 4120 and 4220 All platforms Policy based routing (PBR) for IPv4 All platforms Protocol-based VLANS All platforms PSTag All platforms All platforms All platforms All platforms RIPv1/v2 All platforms except 4120 and 4220 All platforms	Edge and Advanced Edge licenses. See the	
IPv6 interworking—IPv6-to-IPv4 and IPv6-in-IPv4 configured tunnels  IPv6 DAD without CLI management  All platforms  All platforms except 4120 and 4220  All platforms  All platforms except 4120 and 4220  All platforms  All platforms except 4120 and 4220  All platforms  All platforms  All platforms except 4120 and 4220  All platforms except 4120 and 4220  All platforms except 4120 and 4220  All platforms  All platforms	IPv4 Duplicate Address Detection (DAD)	All platforms
IPV4 configured tunnels IPV6 DAD without CLI management All platforms  Keychain Manager Local-only, user-created virtual routers (VR) All platforms  Local-only, user-created virtual routers (VR) Multi-Switch Link Aggregation Group (MLAG) All platforms except 4120 and 4220  Multinetting for forwarding All platforms  ONEPolicy All platforms ONEPv2-Edge (limited to max of 4 active interfaces) OSPFv2-Edge (limited to max of 4 active interfaces) All platforms except 4120 and 4220 OSPFv3-Edge (limited to max of 4 active interfaces) All platforms except 4120 and 4220 OSPFv3-Edge (limited to max of 4 active interfaces) PIM—Universal switches are not subject to the maximum number of PIM IPv4 interfaces (4) that pertains to other switch models. PIM-SM-Edge All platforms except 4120 and 4220 PIM snooping Note: This feature has limitations in the Base license. See the Switch Engine v33.1.1 User Guide. Policy based routing (PBR) for IPv4 Policy based routing (PBR) for IPv4 All platforms Protocol-based VLANs PSTag S420 and 5520 Python scripting All platforms RIP vI/v2 All platforms except 4120 and 4220 Routing access policies All platforms All platforms	IPv6 unicast routing, including static routes	All platforms
IPv6 DAD with CLI management Keychain Manager Local-only, user-created virtual routers (VR) Multi-Switch Link Aggregation Group (MLAG) Multinetting for forwarding All platforms All platforms ONEPolicy OSPFv2-Edge (limited to max of 4 active interfaces) OSPFv2 Auto-peering All platforms except 4120 and 4220 OSPFv3-Edge (limited to max of 4 active interfaces) All platforms except 4120 and 4220 OSPFv3-Edge (limited to max of 4 active interfaces) All platforms except 4120 and 4220 OSPFv3-Edge (limited to max of 4 active interfaces) All platforms except 4120 and 4220 INDEPOSITION OF PROPERTY		All platforms except 4120 and 4220
Keychain Manager Local-only, user-created virtual routers (VR) All platforms Multi-Switch Link Aggregation Group (MLAG) Multinetting for forwarding All platforms ONEPolicy ONEPolicy All platforms All platforms OSPFV2-Edge (limited to max of 4 active interfaces) OSPFv2 Auto-peering OSPFv3-Edge (limited to max of 4 active interfaces) All platforms except 4120 and 4220 OSPFv3-Edge (limited to max of 4 active interfaces) All platforms except 4120 and 4220 Interfaces) All platforms except 4120 and 4220 All platforms except 4120 and 4220 Interfaces) All platforms except 4120 and 4220 Interfaces Interfaces All platforms except 4120 and 4220 Interfaces All platforms except 4120 and 4220 Interfaces Interfaces Interfaces All platforms except 4120 and 4220 Interfaces Interf	IPv6 DAD without CLI management	All platforms
Local-only, user-created virtual routers (VR)  Multi-Switch Link Aggregation Group (MLAG)  Multinetting for forwarding  All platforms  ONEPolicy  OSPFV2-Edge (limited to max of 4 active interfaces)  OSPFv3-Edge (limited to max of 4 active interfaces)  OSPFv3-Edge (limited to max of 4 active interfaces)  PIM—Universal switches are not subject to the maximum number of PIM IPv4 interfaces (4) that pertains to other switch models.  PIM-SM-Edge  PIM snooping  Note: This feature has limitations in the Base license. See the Switch Engine v33.1.1 User Guide.  Policy based routing (PBR) for IPv4  Policy based routing (PBR) for IPv6  Protocol-based VLANs  PSTag  S420 and 5520  Python scripting  All platforms except 4120 and 4220  All platforms  RIP v1/v2  All platforms except 4120 and 4220  All platforms  All platforms  Policy based routing (PBR) for IPv6  All platforms  All platforms except 4120 and 4220  All platforms except 4120 and 4220  All platforms except 4120 and 4220	IPv6 DAD with CLI management	All platforms
Multi-Switch Link Aggregation Group (MLAG)  Multinetting for forwarding  All platforms  ONEPolicy  All platforms  ONEPolicy  All platforms  OSPFV2-Edge (limited to max of 4 active interfaces)  OSPFV2 Auto-peering  OSPFV2 Auto-peering  OSPFV3-Edge (limited to max of 4 active interfaces)  OSPFV3-Edge (limited to max of 4 active interfaces)  PIM—Universal switches are not subject to the maximum number of PIM IPv4 interfaces (4) that pertains to other switch models.  PIM-SM-Edge  PIM snooping  All platforms except 4120 and 4220  All platforms except 4120 and 4220  Note: This feature has limitations in the Base license. See the Switch Engine v33.11 User Guide.  Policy based routing (PBR) for IPv4  Policy based routing (PBR) for IPv6  All platforms  Protocol-based VLANs  All platforms  PSTag  5420 and 5520  Python scripting  All platforms except 4120 and 4220  RIPng  All platforms except 4120 and 4220  All platforms  All platforms except 4120 and 4220	Keychain Manager	All platforms
Multinetting for forwarding  ONEPolicy  ONEPolicy  All platforms  All platforms  ONEPolicy  OSPFv2-Edge (limited to max of 4 active interfaces)  OSPFv2 Auto-peering  OSPFv3-Edge (limited to max of 4 active interfaces)  PIM—Universal switches are not subject to the maximum number of PIM IPv4 interfaces (4) that pertains to other switch models.  PIM-SM-Edge  PIM snooping  All platforms except 4120 and 4220  All platforms  Policy based routing (PBR) for IPv4  All platforms  Policy based routing (PBR) for IPv6  All platforms  Protocol-based VLANs  All platforms  PSTag  S420 and 5520  Python scripting  All platforms except 4120 and 4220  All platforms  RIP vI/v2  All platforms except 4120 and 4220	Local-only, user-created virtual routers (VR)	4120, 4220, 5320-24T/24P
ONEPolicy OSPFv2-Edge (limited to max of 4 active interfaces) OSPFv2 Auto-peering OSPFv3-Edge (limited to max of 4 active interfaces) OSPFv3-Edge (limited to max of 4 active interfaces) OSPFv3-Edge (limited to max of 4 active interfaces) All platforms except 4120 and 4220 All platforms except 4120 and 4220 INDEPORT Edge All platforms except 4120 and 4220 All platforms All platforms Policy based routing (PBR) for IPv4 All platforms Policy based routing (PBR) for IPv6 All platforms Protocol-based VLANs All platforms PSTag S420 and 5520 Python scripting All platforms RIP vl/v2 All platforms except 4120 and 4220 RIPng All platforms except 4120 and 4220 All platforms except 4120 and 4220 Routing access policies All platforms	Multi-Switch Link Aggregation Group (MLAG)	All platforms except 4120 and 4220
OSPFv2-Edge (limited to max of 4 active interfaces)  OSPFv2 Auto-peering  All platforms except 4120 and 4220  OSPFv3-Edge (limited to max of 4 active interfaces)  PIM—Universal switches are not subject to the maximum number of PIM IPv4 interfaces (4) that pertains to other switch models.  PIM-SM-Edge  PIM snooping  Note: This feature has limitations in the Base license. See the Switch Engine v33.1.1 User Guide.  Policy based routing (PBR) for IPv4  Policy based routing (PBR) for IPv4  All platforms  Protocol-based VLANs  All platforms  PSTag  S420 and 5520  Python scripting  All platforms  RIP vI/v2  RIPng  All platforms except 4120 and 4220  All platforms  All platforms except 4120 and 4220	Multinetting for forwarding	All platforms
interfaces)  OSPFv2 Auto-peering  All platforms except 4120 and 4220  OSPFv3-Edge (limited to max of 4 active interfaces)  PIM—Universal switches are not subject to the maximum number of PIM IPv4 interfaces (4) that pertains to other switch models.  PIM-SM-Edge  All platforms except 4120 and 4220  PIM snooping  All platforms except 4120 and 4220  Note: This feature has limitations in the Base license. See the Switch Engine v33.1.1 User Guide.  Policy based routing (PBR) for IPv4  All platforms  Policy based routing (PBR) for IPv6  Protocol-based VLANs  PSTag  S420 and 5520  Python scripting  RIP v1/v2  All platforms except 4120 and 4220  All platforms  RIP v1/v2  All platforms except 4120 and 4220  All platforms	ONEPolicy	All platforms
OSPFv3-Edge (limited to max of 4 active interfaces)  PIM—Universal switches are not subject to the maximum number of PIM IPv4 interfaces (4) that pertains to other switch models.  PIM-SM-Edge  All platforms except 4120 and 4220  PIM snooping  Note: This feature has limitations in the Base license. See the Switch Engine v33.1.1 User Guide.  Policy based routing (PBR) for IPv4  Policy based routing (PBR) for IPv6  All platforms  Protocol-based VLANs  PSTag  Python scripting  All platforms  All platforms except 4120 and 4220  All platforms except 4120 and 4220  All platforms  All platforms except 4120 and 4220  All platforms  All platforms		All platforms except 4120 and 4220
interfaces)  PIM—Universal switches are not subject to the maximum number of PIM IPv4 interfaces (4) that pertains to other switch models.  PIM-SM-Edge  All platforms except 4120 and 4220  PIM snooping  Note: This feature has limitations in the Base license. See the Switch Engine v33.1.1 User Guide.  Policy based routing (PBR) for IPv4  All platforms  Policy based routing (PBR) for IPv6  All platforms  Protocol-based VLANs  PSTag  5420 and 5520  Python scripting  All platforms  RIP v1/v2  All platforms except 4120 and 4220  Routing access policies  All platforms  All platforms  All platforms  All platforms  All platforms	OSPFv2 Auto-peering	All platforms except 4120 and 4220
maximum number of PIM IPv4 interfaces (4) that pertains to other switch models.  PIM-SM-Edge All platforms except 4120 and 4220  PIM snooping All platforms except 4120 and 4220  Note: This feature has limitations in the Base license. See the Switch Engine v33.1.1 User Guide.  Policy based routing (PBR) for IPv4 All platforms  Protocol-based VLANs All platforms  PSTag S420 and 5520  Python scripting All platforms  RIP v1/v2 All platforms except 4120 and 4220  RIPng All platforms except 4120 and 4220  Routing access policies All platforms		All platforms except 4120 and 4220
PIM snooping  Note: This feature has limitations in the Base license. See the Switch Engine v33.1.1 User Guide.  Policy based routing (PBR) for IPv4  All platforms  Policy based routing (PBR) for IPv6  All platforms  Protocol-based VLANs  PSTag  S420 and 5520  Python scripting  All platforms  RIP v1/v2  All platforms except 4120 and 4220  RIPng  All platforms except 4120 and 4220  Routing access policies  All platforms	maximum number of PIM IPv4 interfaces (4)	All platforms except 4120 and 4220
Note: This feature has limitations in the Base license. See the Switch Engine v33.1.1 User Guide.  Policy based routing (PBR) for IPv4 All platforms Policy based routing (PBR) for IPv6 All platforms Protocol-based VLANs All platforms PSTag 5420 and 5520 Python scripting All platforms RIP v1/v2 All platforms except 4120 and 4220 RIPng All platforms except 4120 and 4220 Routing access policies All platforms	PIM-SM-Edge	All platforms except 4120 and 4220
license. See the Switch Engine v33.1.1 User Guide.  Policy based routing (PBR) for IPv4 All platforms Policy based routing (PBR) for IPv6 All platforms Protocol-based VLANs All platforms PSTag 5420 and 5520 Python scripting All platforms RIP v1/v2 All platforms except 4120 and 4220 RIPng Routing access policies All platforms	PIM snooping	All platforms except 4120 and 4220
Policy based routing (PBR) for IPv6 All platforms Protocol-based VLANs All platforms  PSTag 5420 and 5520  Python scripting All platforms  RIP v1/v2 All platforms except 4120 and 4220  RIPng Routing access policies All platforms		
Protocol-based VLANs  All platforms  5420 and 5520  Python scripting  All platforms  RIP v1/v2  All platforms except 4120 and 4220  RIPng  All platforms except 4120 and 4220  All platforms except 4120 and 4220  All platforms	Policy based routing (PBR) for IPv4	All platforms
PSTag 5420 and 5520  Python scripting All platforms  RIP v1/v2 All platforms except 4120 and 4220  RIPng All platforms except 4120 and 4220  Routing access policies All platforms	Policy based routing (PBR) for IPv6	All platforms
Python scripting  All platforms  RIP v1/v2  All platforms except 4120 and 4220  RIPng  All platforms except 4120 and 4220  All platforms except 4120 and 4220  Routing access policies  All platforms	Protocol-based VLANs	All platforms
RIP v1/v2 All platforms except 4120 and 4220 RIPng All platforms except 4120 and 4220 Routing access policies All platforms	PSTag	5420 and 5520
RIPng All platforms except 4120 and 4220 Routing access policies All platforms	Python scripting	All platforms
Routing access policies All platforms	RIP v1/v2	All platforms except 4120 and 4220
	RIPng	All platforms except 4120 and 4220
Route maps All platforms	Routing access policies	All platforms
	Route maps	All platforms

Premier License Features Switch License Features

**Table 5: Switch Engine Base License Features (continued)** 

Switch Engine Software Feature	Supported Platforms
SummitStack (switch stacking using native or dedicated ports)	Not supported
SummitStack-V (switch stacking using dual- purpose data ports)	All platforms. See the specific models listed in the "Support for Alternate Stacking Ports" section of the <i>Switch Engine v33.1.1 User Guide</i> .
SyncE	Not supported
System virtual routers (VRs)	All platforms
UDP Forwarding	All platforms
UDP BootP relay forwarding	All platforms
User-created virtual routers (VRs) Virtual router and forwarding (VRF)	5320-48T/48P, 5420, 5520, 5720, 7520, 7720
VLAN aggregation	All platforms
VRRP	All platforms except 4120 and 4220
VXLAN	All platforms, except 4120 and 4220

## Premier License Features

The Premier License includes the features in the following table:

**Table 6: Switch Engine Premier License Features** 

Switch Engine software feature	Supported platforms
Anycast RP	All platforms except 4120 and 4220
Anycast RP Using PIM (RFC 4610)	All platforms except 4120 and 4220
BGP4 and MBGP (BGP4+) for IPv4 ECMP	All platforms except 4120 and 4220
BGP4 and MBGP (BGP4+) for IPv6	All platforms except 4120 and 4220
EVPN	All platforms except 4120 and 4220
GRE tunneling	All platforms except 4120 and 4220
Integrated Application Hosting (IAH)	ExtremeSwitching 5720, Extreme 7520 and 7720
IS-IS for IPv4	All platforms except 4120 and 4220
IS-IS for IPv6	All platforms except 4120 and 4220
MSDP	All platforms except 4120 and 4220
OSPFv2 "Full" (not limited to 4 active interfaces)	All platforms except 4120 and 4220
OSPFv3 "Full" (not limited to 4 active interfaces)	All platforms except 4120 and 4220
PIM DM "Full"	All platforms except 4120 and 4220

Switch License Features Premier License Features

## **Table 6: Switch Engine Premier License Features (continued)**

Switch Engine software feature	Supported platforms
PIM SM "Full"	All platforms except 4120 and 4220
PIM SSM "Full"	All platforms except 4120 and 4220



# **Feature Licenses**

Network Timing Feature License on page 23 MAC Security Feature License on page 23

The Switch Engine software features are listed in the following table are managed as feature licenses. Feature licenses are distributed in one of the following forms:

- In Switch Engine software (standard software component)—You must purchase a license to use the feature.
- Modular software package (XMOD file, so named because of its .xmod file extension)
   —You must request the XMOD file from your supplier and install it.

For feature license and installation instructions, see *Installing a Modular Software Package* in the *Switch Engine v33.1.1 User Guide*.



#### Note

Secure Shell 2 (SSH2) is not provided as a feature license. It is incorporated into the main Switch Engine software image and is not provided as an XMOD. However, SSH2 contains strong encryption algorithms that heighten the export controls required in the US and other countries. When downloading the Switch Engine software image, you are required to verify that you meet the export clearance requirements. For more information, see *Software Upgrade and Boot Options* in the *Switch Engine v33.1.1 User Guide*.

For more information on SSH2, see *Using Secure Shell 2* in the *Switch Engine v33.1.1 User Guide*.

**Table 7: Switch Engine Feature Licenses** 

Feature License	Feature	Platform support	XMOD Require d
MPLS Feature The MPLS Feature is available as part of the Premier license under the Platform Support column.	<ul> <li>MPLS</li> <li>LDP</li> <li>Static LSPs</li> <li>OSPF-TE</li> <li>MPLS label</li> <li>EXP bit replacement and classification</li> <li>RSVP-TE</li> <li>VPLS / H-VPLS for VLANS</li> <li>VPLS STP redundancy</li> <li>VPLS with ESRP redundancy</li> <li>VPLS with EAPS redundancy</li> <li>Fast Reroute (FRR)</li> <li>Support for PW counters</li> <li>User Virtual Routers</li> <li>L3VPN</li> </ul>	5520, 7520, and 7720. The MPLS Feature is available as part of the Premier License.	No
AVB Feature License	<ul> <li>Generalized         Precision Time         Protocol (GPTP)         </li> <li>Multiple VLAN         Registration         Protocol (MVRP)     </li> </ul>	All platforms, except 4120, 4220, 5320-XT, 7520, and 7720. All Universal Hardware platforms have the AVB Feature License included in the Base License. You do not need to separately purchase and install	No

**Table 7: Switch Engine Feature Licenses (continued)** 

Feature License	Feature	Platform support	XMOD Require d
	<ul><li>Multiple Stream Registration Protocol (MSRP)</li><li>Platform Support</li></ul>	the AVB Feature License for supported Universal platforms.	
Network Timing Feature License See Network Timing Feature License on page 23.	Precision Time Protocol End-to-End Transparent Clock (PTPv2)	5520, 5720, 7520, and 7720 series switches with Premier license.	No
MAC Security License See MAC Security Feature License on page 23.	MAC Security licensing.	See MACsec Platform Support on page 20	No
ExtremeCloud™ IQ Agent	ExtremeCloud IQ provides device discovery, basic monitoring, visibility into homogenous stacking, ability to configure an optional user-defined VR, and address of the server to connect to. For more information about ExtremeCloud IQ, go to https://www.extremenetworks.com/extremecloudiq/.	See ExtremeCloud IQ Platform Support on page 21.	Yes

## MACsec Platform Support

**Table 8: MACsec Supported Platforms** 

Platform	Ports	LRM/ MACsec Adapter Required ?
ExtremeSwitching 5320	Supported on all front-panel ports except stacking ports. Not supported on model 5320-24T-4X-XT.	No
ExtremeSwitching 5420	Supported on all front-panel ports except stacking ports.	No

**Table 8: MACsec Supported Platforms (continued)** 

Platform	Ports	LRM/ MACsec Adapter Required ?
ExtremeSwitching 5520	Supported on all front-panel ports. Not supported on 5520-VIM-4X and 24X 10G ports.	No
ExtremeSwitching 5720	Supported on all front-panel ports except stacking ports.	No
Extreme 7520-48YE-8CE	Supported on all front-panel ports.	No

## ExtremeCloud IQ Platform Support

**Table 9: Supported Platforms** 

Switch Series	Switch Models
4120*	4120-24MW-4Y
	4120-48MW-4Y
4220*	4220-8X
	4220-12P-4X
	4220-12T-4X
	4220-24P-4X
	4220-24T-4X
	4220-48P-4X
	4220-48T-4X
	4220-4MW-8P-4X
	4220-4MW-20P-4X
	4220-8MW-40P-4X
ExtremeSwitching 5320	5320-48T-8XE
	5320-48P-8XE
	5320-24T-8XE
	5320-24P-8XE
	5320-16P-4XE
	5320-16P-4XE-DC
	5320-24T-4X-XT
	5320-24T-24S-4XE-XT

**Table 9: Supported Platforms (continued)** 

Switch Series	Switch Models	
ExtremeSwitching 5420	5420F-8W-16P-4XE	
	5420F-24P-4XE	
	5420F-24S-4XE	
	5420F-24T-4XE	
	5420F-16MW-32P-4XE	
	5420F-16W-32P-4XE	
	5420F-48P-4XE	
	5420F-48P-4XL	
	5420F-48T-4XE	
	5420M-24T-4YE	
	5420M-24W-4YE	
	5420M-16MW-32P-4YE	
	5420M-48T-4YE	
	5420M-48W-4YE	
ExtremeSwitching 5520	5520-24T	
	5520-24W	
	5520-48T	
	5520-48W	
	5520-12MW-36W	
	5520-24X	
	5520-48SE	
	5520-24T-ACDC-BASE	
	5520-48T-ACDC-BASE	
	5520-24X-ACDC-BASE	
	5520-48SE-ACDC-BASE	
ExtremeSwitching 5720	5720-24MW	
	5720-24MXW	
	5720-48MW	
	5720-48MXW	
Extreme Networks 7520	7520-48Y-8C	
	7520-48XT-6C	
	7520-48YE-8CE	
Extreme Networks 7720	7720-32C	

<sup>\* -</sup> See *4000 Series User Guide* for this version of Switch Engine for detailed information on these Cloud-managed devices.

## Network Timing Feature License

The Network Timing Feature License is included with the Premier license and supports the Precision Time Protocol (PTPv2) with transparent clock only.



#### Note

Network-Clock module is required in addition to Network Timing Feature License to enable PTPv2. This is not required for E2E Transparent Clock support in Universal Switches

For more information about PTP, see *Overview of PTP* in the *Switch Engine v33.1.1 User Guide*.

## MAC Security Feature License

Use of the MAC Security (MACsec) feature requires a slot-based MACsec Feature License.

Slot-based MACsec licenses have the following behaviors:

#### **Table 10: MACsec License Behavior**

	No License	License Installed
Standalone Switch	<ul> <li>The command show macsec is the only available command.</li> <li>MACsec cannot be configured or enabled.</li> </ul>	<ul> <li>All MACsec commands are available.</li> <li>MACsec can be configured and enabled.</li> </ul>
Stack	<ul> <li>All MACsec commands are available.</li> <li>MACsec can be configured on MACsec- capable slots.</li> <li>If configured, MACsec cannot be enabled.</li> </ul>	<ul> <li>All MACsec commands are available.</li> <li>MACsec can be configured and enabled on licensed slots.</li> </ul>



#### Note

In a stack, any slot configured with a MACsec-capable module (with configure **slot** slot **module** module\_type) can be configured for MACsec, even if the slot is not physically present, or if the slot is present, but does not have a valid MACsec license installed.