

## Service Release Notes for WiNG 7.3.1.2-003R

**Please Note:** Service releases are made available to fix specific customer reported issues in a timely manner. Service releases are not as extensively tested as main releases (such as 7.2.1.0-015R). The next maintenance or manufacturing release will incorporate all qualifying and preceding service releases.

This document is an addendum to the release notes for the main release 7.3.1.0-046R.

## **CONTENTS**

1. Resolved Issues	
2. Known issues	_
2. Important Notes	2
3. Platforms Supported	2
4. Firmware Upgrade/Downgrade Procedure	2

## 1. RESOLVED ISSUES

## Service Release 7.3.1.2-003R

This service release 7.3.1.2-003R contains critical fixes for both distributed and Campus modes. Extreme Campus Controller (XCC) 4.76.04 release will include this WiNG release. Refer to Extreme Campus Controller 4.76.04.005 Release Note for details.

#### Following is a list of SPRs/CRs fixed in this release:

CRID	Description
WING-42828	Packet capture shows channel and RSSI 0
WING-42919	AP310 not reporting RSSI
WING-42920	AP310 not reporting interferences on 2.4GHz
WING-42961	AP460- Antenna usage changed after upgrade to 7.3.1.1

### Previous Service Release 7.3.1.1-012R



+1 888-257-3000

This service release 7.3.1.1-012R contains critical fixes for both distributed and Campus modes. This release ExtremeCloud Appliance 4.56.09 release will include this WiNG release. Refer to ExtremeCloud Appliance 4.56.09.003 Release Note for details.

#### Following is a list of SPRs/CRs fixed in this release:

CRID	Description
WING-42749	Addressed missing CDP LLDP element under WiNG adoption info
WING-42900	Corrected WING-MIB.mib description for Total system RAM to display in megabytes instead of kilobytes

## 2. KNOWN ISSUES

CQ/ SPR	Headline	Comments
WING-39525	AP4xx: Radio-Share Mode	Disable radio-share on Radio 1 and 2. Enable dedicated sensor on Radio 3.

## 2. IMPORTANT NOTES

None

# 3. PLATFORMS SUPPORTED

This release applies to all platforms released with WiNG 7.3.1.0-046R.

## 4. FIRMWARE UPGRADE/DOWNGRADE PROCEDURE

The method described in this section uses the Command Line Interface (CLI) procedures. To log into the CLI, either SSH, Telnet or serial access can be used.

For detailed upgrade procedure – please refer to WiNG 7.3.1 release notes.

#### Upgrade from WiNG v7x.x.x to WiNG v7.3.1.2

- 1. Copy the controller image to your tftp/ftp server.
- 2. Use the —upgrade ftp://<username>:<password>@<ip address of server>/<name of file>||, or —upgrade tftp://<ip address of server>/<name of file> command from CLI or Switch->Firmware->Update Firmware option from the GUI. You may need to specify the username and password for your ftp server.

+1 888-257-3000



**ADVANCE WITH US** 

3. Restart the controller. From CLI the command is —reload.

© Extreme Networks. 2019. All rights reserved.